


CO₂ Extinguisher B Portable CO₂ extinguishers

The CO₂ extinguisher is effective in fighting flammable liquids and electric fires. Carbon dioxide extinguisher works by suffocating the fire. Carbon dioxide displaces oxygen in the air. The extinguishing agent leaves no residue behind when used. CO₂ extinguishers cover type B fires.



Benefits

Applications for the marine, inland shipping and offshore market

- electrical switch boards
 - bridge
 - welding areas
-

Features

- carbon dioxide is a clean agent that leaves no traces, thus ideal for fighting fires involving electronic & hi-tech equipment
 - allows intermittent and repeated operation
 - equipped with a brass valve head complete with an overpressure safety valve
 - equipped with a squeeze-type valve, conical snow horn, and carrying handle
 - high quality surface treatment and red polyester coating
-

Special features for 2 kgs extinguishers

- a flat wall mounting bracket is included
-

Special features for 5 kgs extinguishers

- to be used with a special marine wall bracket (not included)

Accessories



Cabinets

Cabinets are made of durable GRP or polyethylene material. The GRP cabinets are designed for tough offshore conditions, these cabinets are rated to IPX6 as certified by TÜV. The cabinets can be used for multi purposes such as storage of fire or safety equipment. The cabinets are deliverable in various sizes, with a green or red door.



Brackets

Wall brackets for 2 till 12 kgs fire extinguishers. For all types of extinguishers: powder, foam, CO₂, watermist and wet chemical foam.

Technical Data

	2 kgs	5 kgs
Manufacturer / Model	Bavaria / Col X-K 2	Bavaria / COL X-K
Extinguisher	Portable CO ₂ fire extinguisher	Portable CO ₂ fire extinguisher
Type	Stored pressure operated	Stored pressure operated
Capacity	2 kgs	5 kgs
Fire class / Rating	34B	89B
Propellant gas	CO ₂	CO ₂
Discharge time	approx. 8 seconds	15 seconds
Throw length	3 – 4 meters	4 meters
Working pressure	65 bar	65 bar
Suitable for electrical equipment	Up to 1000 Volt	Up to 1000 Volt
Extinguishing agent	CO ₂	CO ₂
Temperature range	-30°C to +60°C	-30°C to +60°C
Approx gross weight	7.1 kgs	14.2 kgs
Approx dispatch weight	8.1 kgs	14.7 kgs
Approx unit dimension	250 x 110 x 550 mm (l x w x h)	260 x 140 x 690 mm (l x w x h)
Color	Red, 100% polyester coating	Red (RAL3000)
Approvals	DIN/EN3 MED	DIN EN3 & CE 0036 MED

Ordering Information

Description	IMPA no.	Articlenr
Dräger CO ₂ Extinguisher 2 kgs B, including a flat wall mounting bracket		SG00141
Dräger CO ₂ Extinguisher 5 kgs B	331042	SG00142
Marine bracket for CO ₂ extinguisher 2 kgs, including strap		SG00338
Marine bracket for CO ₂ 5 kgs		SG00337
Cover for fire extinguisher 2 kgs / 5 kgs		SG00311
GRP storage cabinet: DMO-35 2 kgs / 5 kgs		SG02030
Polyethylene fire extinguisher cabinet JBXF-83, red door 2 kgs / 5 kgs		SG02432
Spray and hose: 2 kgs CO ₂		SG00382
Spray and hose: 5 kgs CO ₂		SG00383

Service and support

Dräger offers 24/7 service and support, including full certification on all Dräger and non-Dräger products. Contact us for more details.

Notes

Notes

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Safety Asia Pte Ltd
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL

AND SOUTH AMERICA
Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377 9100
Fax +507 377 9130
contactcsa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

